ANACONDA
PIPE AND HOSE

VISIT SITE NOW

SLURRY DISCHARGE 4” HOSE

Application	Ideal for discharge of seawater, sand, abrasive materials due to more flexibility and high wear resistance.
Technical	Tube: NR, BR, SBR Reinforcement: High tensile strength fabrics with helix steel wire Cover: NR, CR No Negative Pressure
Safe	3:1
Working	20˚C to 80˚C
Flange	Standard ANSI 150 PSI Fixed Flange

Inner Diameter	Outer Diameter	Inner Layer Thickness	Working Pressure	Length	Weight
4” (102 mm)	5” (128 mm)	5/16” (8 mm)	110 PSI	33’ (10 m)	199 lbs (90.3 kg)

STANDARD ANSI 150 PSI FLANGE SPECIFICATION

Normal Diameter	Number of Bolt Holes	Diameter of Bolt Holes	Flange Thickness	Outer Diameter of Flange
4” (102 mm)	8	5/16” (18 mm)	0.89” (22.5 mm)	9” (228 mm)

BEND RADIUS

Normal Diameter	Range
4” (102 mm)	24.5” – 40” (620 mm – 1020 mm)

CONTACT US

(619) 201-8311

sales@anacondapipeandhose.com