

# ANACONDA

PIPE AND HOSE

VISIT SITE NOW



## ARMOUR GUARD®

### Heavy Duty Industrial Discharge Hose

Anaconda Armour Guard® is a lay-flat, flexible water discharge hose that brings impressive flow to any situation. It combines the lightweight, compact features of a unique nitrile PVC blend with enhanced durability and abrasion resistance as compared to conventional rubber hose. Armour Guard features a heavy-duty, onepiece design with all-synthetic, extruded-through-the-weave materials. This allows the hose to expand under pressure, decreasing friction loss and increases water flow. The ozone-resistant synthetic rubber liner and cover totally encase and protect the high-performance inner nylon reinforcement from the effects of abrasion, chemicals and heat. Armour Guard cleans easily and offers ease of maintenance. The standard color is black.


#### UNIQUE DESIGN FEATURES:

- Ozone resistance
- Abrasion resistance
- Heat resistance
- Resists fuels, oil, and wide range of chemicals

*Step up your water delivery!*

 **AMERICAN MADE TOUGH.™**

**CONTACT US**

 (619) 592-8636

 [anacondapipeandhose.com](http://anacondapipeandhose.com)

## ARMOUR GUARD®



### FEATURES:

#### Long Service Life

Nitrile-rubber cover eliminates additional weight issues caused by water pick up during use and greatly increases abrasion resistance, providing a long service life.

#### Easy to Store

Required minimal storage space

#### Temperature range -36°F to +120°F

Peak performance in a variety of environments, with optimum operating temperatures ranging from -36°F to 120°F

#### Anti-Burst Technology

Fully protected high tensile yarns for improved working pressure rating and drag resistance.

#### Durable Construction

A unique nitrile PVC blend with enhanced durability and abrasion resistance as compared to conventional rubber hose. Armour Guard features a heavy-duty, one-piece design with all-synthetic, extruded-through-the-weave materials.

### TECHNICAL SPECIFICATIONS:

Size		Service		Pressure Proof		Burst		Bowl Size		Weight (50'/15M)		Coil Diameter (50'/15M)	
inch	mm	psi	kpa	psi	kpa	psi	kpa	inch	mm	lbs/ft	kg	inch	mm
1 1/2	38	300	2,100	600	4,200	900	6,300	1 13/16	46	14	6.4	14 3/4	375
2 1/2	64	300	2,100	600	4,200	900	6,300	2 7/8	73	26	11.8	16 1/2	419

Anaxonda Pipe and Hose Company maintains ongoing product improvement and development programs. Therefore Anaconda reserves the right to modify any product or specification without prior notice. If necessary, please contact Bulldog Hose Company customer service to ensure that all claims and technical data are current.

NITRILE PVC BLEND EXTRUDED THROUGH-THE-WEAVE MATERIAL PROVIDES SUPERIOR RESISTANCE TO OZONE AND ABRASION AS WELL AS EXTREME DURABILITY IN HARSH ENVIRONMENTS

